



FABCON LIQUID

(ChemWatch name: FABCON)

ChemWatch Material Safety Data Sheet (REVIEW)
Issue Date: Thu 7-Apr-2005

CHEMWATCH 4718-11
CD 2005/2 Page 1 of 9

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

FABCON LIQUID

STATEMENT OF HAZARDOUS NATURE

Not considered a Hazardous Substance according to the criteria of the New Zealand Hazardous Substances New Organisms legislation.

SYNONYMS

?


























PRODUCT USE

Fabric conditioning and softener. Reduces static.

SUPPLIER

Company: Andrew Limited
Address:
3 Porana Road
Glenfield
AUCKLAND
Telephone: 09 444 3733
Telephone: 0800 429 628
Emergency Tel: 0800 243 622
Fax: 09 444 3838

HAZARD RATINGS

Flammability					
Toxicity					
Body Contact					
Reactivity					
Chronic					
SCALE:	Min/Nil=0	Low=1	Moderate=2	High=3	Extreme=4

Section 2 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HAZARD

Not hazardous
No hazards determined by Chemwatch using GHS/HSNO criteria

PRECAUTIONARY STATEMENTS

continued...

FABCON LIQUID

(ChemWatch name: FABCON)

ChemWatch Material Safety Data Sheet (REVIEW)

Issue Date: Thu 7-Apr-2005

CHEMWATCH 4718-11

CD 2005/2 Page 2 of 9

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
additives, unregulated		1-9
surfactant, unregulated		1-9
perfume		<1
dye		<1
water	7732-18-5	>60

NOTE: Manufacturer has supplied full ingredient information to allow CHEMWATCH assessment.

Section 4 - FIRST AID MEASURES

SWALLOWED

- Immediately give a glass of water.
- First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

EYE

If this product comes in contact with eyes:

- Wash out immediately with water.
- If irritation continues, seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

If skin or hair contact occurs:

- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Other measures are usually unnecessary.

NOTES TO PHYSICIAN

Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- There is no restriction on the type of extinguisher which may be used. Use extinguishing media suitable for surrounding area.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves for fire only.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use fire fighting procedures suitable for surrounding area.
- DONOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.

continued...

FABCON LIQUID

(ChemWatch name: FABCON)

ChemWatch Material Safety Data Sheet (REVIEW)

Issue Date: Thu 7-Apr-2005

CHEMWATCH 4718-11

CD 2005/2 Page 3 of 9

Section 5 - FIRE FIGHTING MEASURES

- Equipment should be thoroughly decontaminated after use.

FIRE/EXPLOSION HAZARD

- Non combustible.
- Not considered to be a significant fire risk.
- Expansion or decomposition on heating may lead to violent rupture of containers.
- Decomposes on heating and may produce toxic/irritating fumes.
- May emit acrid smoke.

FIRE INCOMPATIBILITY

None known.

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

Slippery when spilt.

- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable labelled container for waste disposal.

MAJOR SPILLS

Slippery when spilt.

Minor hazard.

- Clear area of personnel.
- Alert Fire Brigade and tell them location and nature of hazard.
- Control personal contact by using protective equipment as required.
- Prevent spillage from entering drains or water ways.
- Contain spill with sand, earth or vermiculite.
- Collect recoverable product into labelled containers for recycling.
- Absorb remaining product with sand, earth or vermiculite and place in appropriate containers for disposal.
- Wash area and prevent runoff into drains or waterways.
- If contamination of drains or waterways occurs, advise emergency services.

EMERGENCY RESPONSE PLANNING GUIDELINES (ERPG)

The maximum airborne concentration below which it is believed that nearly all individuals could be exposed for up to one hour WITHOUT experiencing or developing

life-threatening health effects is:

water 500 mg/m³

irreversible or other serious effects or symptoms which could impair an individual's ability to take protective action is:

water 500 mg/m³

other than mild, transient adverse effects without perceiving a clearly defined odour is:

water 500 mg/m³

continued...

FABCON LIQUID

(ChemWatch name: FABCON)

ChemWatch Material Safety Data Sheet (REVIEW)

Issue Date: Thu 7-Apr-2005

CHEMWATCH 4718-11

CD 2005/2 Page 4 of 9

Section 6 - ACCIDENTAL RELEASE MEASURES

The threshold concentration below which most people will experience no appreciable risk of health effects:

water 500 mg/m³

American Industrial Hygiene Association (AIHA)

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Limit all unnecessary personal contact.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Avoid contact with incompatible materials.
- When handling, DONOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

SUITABLE CONTAINER

- Polyethylene or polypropylene container.
- Packing as recommended by manufacturer
- Check all containers are clearly labelled and free from leaks.

STORAGE INCOMPATIBILITY

Avoid contamination of water, foodstuffs, feed or seed.

STORAGE REQUIREMENTS

- Store in original containers.
 - Keep containers securely sealed.
 - Store in a cool, dry, well-ventilated area.
 - Store away from incompatible materials and foodstuff containers.
 - Protect containers against physical damage and check regularly for leaks.
 - Observe manufacturer's storing and handling recommendations.
-

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

No data available for water as (CAS: 7732-18-5)

Not available. Refer to individual constituents.

INGREDIENT DATA

WATER:

No exposure limits set by NOHSC or ACGIH.

continued...

FABCON LIQUID

(ChemWatch name: FABCON)

ChemWatch Material Safety Data Sheet (REVIEW)


Issue Date: Thu 7-Apr-2005

CHEMWATCH 4718-11

CD 2005/2 Page 5 of 9

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

PERSONAL PROTECTION



EYE

No special equipment for minor exposure i.e. when handling small quantities.

•OTHERWISE:

- Safety glasses with side shields.
- Contact lenses pose a special hazard; soft lenses may absorb irritants and all lenses concentrate them.

HANDS/FEET

No special equipment needed when handling small quantities.

OTHERWISE: Wear general protective gloves, eg. light weight rubber gloves.

OTHER

No special equipment needed when handling small quantities.

OTHERWISE:

- Overalls.
- Barrier cream.
- Eyewash unit.

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the computer-generated selection: water

Protective Material CPI *.

BUTYL	A
NEOPRENE	A
VITON	A
PVA	C
NATURAL RUBBER	C

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information

continued...

FABCON LIQUID

(ChemWatch name: FABCON)

ChemWatch Material Safety Data Sheet (REVIEW)

Issue Date: Thu 7-Apr-2005

CHEMWATCH 4718-11

CD 2005/2 Page 6 of 9

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

None under normal operating conditions.

General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant: solvent, vapours, degreasing etc., evaporating from tank (in still air)	Air Speed: 0.25-0.5 m/s (50-100 f/min)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood - local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

continued...

FABCON LIQUID

(ChemWatch name: FABCON)

ChemWatch Material Safety Data Sheet (REVIEW)

Issue Date: Thu 7-Apr-2005

CHEMWATCH 4718-11

CD 2005/2 Page 7 of 9

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Yellow liquid with a perfumed odour; mixes with water.

PHYSICAL PROPERTIES

Liquid.

Mixes with water.

Molecular Weight: Not Applicable

Melting Range (°C): Not Available

Solubility in water (g/L): Miscible

pH (1% solution): Not Available

Volatile Component (%vol): >60

Relative Vapour Density (air=1): Not Available

Lower Explosive Limit (%): Not Applicable

Autoignition Temp (°C): Not Applicable

State: Liquid

Boiling Range (°C): Not Available

Specific Gravity (water=1): Not Available

pH (as supplied): 4.5-5.5

Vapour Pressure (kPa): Not Available

Evaporation Rate: Not Available

Flash Point (°C): Not Applicable

Upper Explosive Limit (%): Not Applicable

Decomposition Temp (°C): Not Available

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

(No Oral LD50, any animal species) The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (eg. liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.

EYE

Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).

SKIN

The material is not thought to produce adverse health effects or skin irritation

continued...

FABCON LIQUID

(ChemWatch name: FABCON)

ChemWatch Material Safety Data Sheet (REVIEW)

Issue Date: Thu 7-Apr-2005

CHEMWATCH 4718-11

CD 2005/2 Page 8 of 9

Section 11 - TOXICOLOGICAL INFORMATION

following contact (as classified by EC Directives using animal models).
Nevertheless, good hygiene practice requires that exposure be kept to a minimum
and that suitable gloves be used in an occupational setting.

INHALED

Not normally a hazard due to non-volatile nature of product.

CHRONIC HEALTH EFFECTS

Long-term exposure to the product is not thought to produce chronic effects
adverse to the health (as classified by EC Directives using animal models);
nevertheless exposure by all routes should be minimised as a matter of course.

TOXICITY AND IRRITATION

Not available. Refer to individual constituents.

unless otherwise specified data extracted from RTECS - Register of Toxic Effects
of Chemical Substances

WATER:

No significant acute toxicological data identified in literature search.

Section 12 - ECOLOGICAL INFORMATION

Refer to data for ingredients, which follows:

WATER:

No data for water.

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible or consult manufacturer for recycling options.
 - Consult State Land Waste Management Authority for disposal.
 - Bury residue in an authorised landfill.
 - Recycle containers if possible, or dispose of in an authorised landfill.
-

Section 14 - TRANSPORTATION INFORMATION

Shipping Name:

None

Transport Hazard Class: None, None

UN/NA Number: None

ADR Number: None

Packing Group: None

Labels Required:

Additional Shipping Information:

International Transport Regulations:

IMO: None

HAZCHEM

None

continued...

FABCON LIQUID

(ChemWatch name: FABCON)

ChemWatch Material Safety Data Sheet (REVIEW)

Issue Date: Thu 7-Apr-2005

CHEMWATCH 4718-11

CD 2005/2 Page 9 of 9

Section 15 - REGULATORY INFORMATION

REGULATIONS

water (CAS: 7732-18-5) is found on the following regulatory lists:
New Zealand Transferred List of Single Component Substances

Section 16 - OTHER INFORMATION

NEW ZEALAND POISONS INFORMATION CENTRE
0800 POISON (0800 764 766)
NZ EMERGENCY SERVICES: 111

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: Thu 7-Apr-2005

Print Date: Fri 1-Jul-2005