



tapes
gloves
work protection

technical data sheet

double sided solvent acrylic tissue tape



specifications

carrier
non woven tissue

liner
white silicone coated
paper

adhesive
solvent acrylic

adhesion to steel
20 n/25 mm

minimum application
temperature
10°C

resistance to solvents &
chemicals
resistant to most oils,
grease, fuels, weak acids,
salts and alkalis

thickness (adhesive and
carrier)
100 microns

temperature resistance
-40°C to +80°C, 140°C short
term (>30 mins)

shelf life
2 years (at 20°C and 50%
relative humidity)

product code: S403

description

non woven tissue carrier coated with solvent acrylic adhesive. the adhesive is resistant to u.v light, ageing, and temperatures of up to 140°C short term, 80°C longer term. the adhesive is suitable for a wide range of applications to a number of substrates, including harder to stick to surfaces.

Areas of use

the adhesive is suitable for a wide range of applications to a number of substrates, including harder to stick to surfaces including low energy substrates such as opp, pp and pe. good for irregular and textured surfaces, including fabrics and heavy boards. it has good temperature resistance and high/tack shear adhesive.



tapes
gloves
work protection

technical data sheet

conditions of use

for best results apply self adhesive tapes between 15°C and 25°C in a dry environment. application surfaces must be dry and free from dust and particles. do not apply on surfaces treated or contaminated by anti-adhesives. do not use paint containing additives which could reduce the adhesive properties. avoid contact with surfaces containing plasticizers or other chemical agents not compatible with the tape. in cases of rough or irregular surfaces, it is better to use a tape with a higher quantity of adhesive. care must be taken with reference to removability without residue and working conditions of the self adhesive tape.

tape storage

suggested storage temperature shall range between 15°C and 25°C with maximum relative humidity of 65%. material shall be stored away from heat sources and possible kept in the original package, avoiding light exposure as well. when temperatures are lower than suggested, it is always required to recondition the adhesive tape to normal temperatures before use.

tape shelf life

self-adhesive tapes technical features are generally not permanent but remain at their best for a minimum of 12 months, if stored according to suggested conditions and avoiding extreme environmental conditions such as quick and sudden temperature changes, extremely high or low temperatures, high levels of humidity, etc.

the information provided is based on our experience and tape industry knowledge. it is given in goodwill but is not intended as a guarantee or warranty. all end users should ensure themselves that the product is suitable for their own particular application before using.

All **selfgard™** and **pomona® products** are trademarks of Pomona Group Ltd and are under license in New Zealand.